

## DMN700W

Manual callpoint, flush mount, white, free contact, break glass

### General

---

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new MCP indoor call point range.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options and approvals

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard



### Standard Features

---

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

# DMN700W

Manual callpoint, flush mount, white, free contact, break glass

## Specifications

Cable Termination	0.5 - 2.5 mm <sup>2</sup>
Max. contact rating (resistive load)	2A @ 30 VDC
Series resistor	NA
<b>Mechanical</b>	
Material	PC/ABS
Weight	110g
Colour	White
<b>Environmental</b>	
Operating temperature	-10°C to +55°C
Storage temperature	-10°C to +55°C
Relative humidity (non-condensing)	0-95%
IP Rating	IP24D

## Ordering Information

Part No.	Description
DMN700W	Manual callpoint, flush mount, white, free contact, break glass
DM788W	Surface mount box without connectors, WHITE
DM711	EN54 universal glass ARITECH branded
DM715	EN54 Universal MCP Glass (without branding)
DMN782	Hinged transparent MCP protection cover
DMN784	(10 pack) Replacement Test Key for Manual Call Points
DMN798	Breakable Seal for Manual Call Points
DMN800	Resettable Element for Manual Call Point