


TECHNOLOGY - QUALITY - INNOVATION - VALUE



ALEPH'S GLOBAL DETECTION PRODUCT GUIDE









ALEPH'S PHOTOELECTRIC OUTDOOR BEAMS

Aleph Outdoor Beams feature sealed optics, an adjustable alarm interrupt, and metered voltage output for alignment purposes. They provide reliable detection even in poor weather conditions, and are suitable for surface or pole mounting (hardware is included). Units are designed to withstand temperature extremes from -25 °C to 55 °C. Non-polarized operating voltage is 10.5 to 30 VDC or 9 to 18 VAC. Specified beam range is doubled for indoor installations.



MY-40 / MY-60

- 30m / 60m Range
- Dual Beam Pulsed Infrared
- Alarm Trips Only When Both Beams Are Interrupted
- NO / NC (SPDT Form "C")
 Dry Contact Relay Output
- Adjustable Beam Response Time
- No Heater Required
- Internal / External Use

ALEPH'S PHOTOELECTRIC OUTDOOR BEAMS

XA-30D / XA-60D / XA-80D / XA-100D

- 30m / 60m / 80m / 100m Range
- Sensitivity Monitor
- Dual Beam Pulsed Infrared
- Adjustable Beam Interruption Time
 40 msec to 700 msec
- Built-in View Finder For Alignment
- Internal / External Use





ALEPH'S PHOTOELECTRIC OUTDOOR BEAMS



XA-031D / XA-061D / XA-081D / XA-101D

- 30m / 60m / 80m / 100m Range
- 4 Channel Selectable Frequency
- Dual Beam Pulsed Infrared
- High Sensitivity Calibration
- Adjustable Beam Response Time
- Buzzer For Ease Of Alignment
- Internal / External Use

ALEPH'S PHOTOELECTRIC OUTDOOR BEAMS

PE-30T / PE-60T

- 30m / 60m Range
- 4 Channel Selectable Frequency
- Stackable Beams
- Dual Beam Pulsed Infrared
- Alarm Trips Only When Both Beams Are Interrupted
- NO / NC (SPDT Form "C")
 Dry Contact Relay Output
- Adjustable Beam Response
 Time
- Built-in Alignment Center
- Internal / External Use



QT-40E / QT-60E / QT-40ESL PET IMMUNE QUAD TECH INTRUSION DETECTORS



Aleph QT-40E/QT-60E/QT-40ESL QUAD TECH INTRUSION DETECTORS

- QMA Qualified Motion Analysis
- Rock Solid RFI Immunity
- Dual Slope Temperature Compensation
- 100lb Pet Immune
- Multi-Function LED

Ambient Temperature Detection Self Dimming LED

• QT-40ESL: Lights your path - Safety

Available with 40-foot and 60-foot protection patterns, the QT Series intrusion detectors provide high quality PIR+Microwave security at outstanding value. ALEPH's unique "QT" signal processing evaluates PIR and Microwave information while factoring in ambient temperature and light for superior "Quad-Tech" performance.

PET IMMUNE INFRARED DETECTORS



ALEPH AL-40E

PIR Intrusion Detectors

- QMA Qualified Motion Analysis
- Rock Solid RFI Immunity
- Dual Slope Temperature Compensation
- 100lb Pet Immune
- Current Consumption 4mA
- Multi-Function LED
 Ambient Temperature Detection
 Self Dimming LED
- Tamper Switch



ALEPH AL44

PIR Intrusion Detectors

- QMA-Qualified Motion Analysis
- Rock-solid RFI immunity
- Digital Operating System Dual slope Temperature Compensation
- 100lb Pet Immune
- Lighting Protection
- 40 X 56 Detection Area

ALEPH'S OUTDOOR DUAL TECHNOLOGY DETECTOR



XC-1XTE

- 100 lb Pet Immune
- Dual Technology
- Outdoor PIR / Microwave
- 2 Form C Relays
- UV / Waterproof
- PIR sensitivity
- Pulse Count selectable
- Selectable Dual Mode / Disable LED
- Selectable Enable / Disable LED
- 40' L X 56' W detection distance
- Pattern Recognition

HIGH IMPACT MAGNETIC CONTACTS

High Impact means, no loss of performance due to adverse stress caused by building movement, sudden impacts, or temperature changes.

SURFACE MOUNTS - WIRE LEADS



1" Gap DC-4511

Dimensions - Mag Cover 3.4" L x 1.2" W x .75" H Magnet - 2.1" L x .6" W x .7" H / Switch - .4" Dia 2.6" L 1 unit per pack



DC-1561

1" Gap

Surface Mount w/ Flange - Matching Magnet Self Adhesive / Nail Mount / 12" Side Wire Leads Dimensions -1 3/32" L x 1/2" D x 1/4" H 10 Per Pack



PS-1541WG

1" Gap

Surface Mount - 11/2" L \times 3/8" D \times 9/32" H Self Adhesive Mount / wire leads

SURFACE MOUNTS - TERMINALS



11/4" Gap PS-1561

Surface Screw Mount - 4" L x 9/16" W x 9/16" H Concealed Terminals & Screws



11/4" Gap PS-1523

Surface Screw Mount 2 Concealed Terminals & Screws
Concealed Terminals & Form C use Model - PS-1525)



DC-2541

11/4" Gap

1" Gap

1" Gap

Screw Mount - 21/2" L x 3/4" W x 5/8" H Covers, Spacers, & Mounting Screws Included Matching Magnet (Form C Use Model PS-1533)



DC-2531

1" Gap

Tape /Screw Mount - 2" L x 3/8" W x 1/4" H Adhesive Tape & Mounting Screws Included Matching Magnet 10 Per Pack

PRESS FIT - WIRE LEADS



DC-1611 WG

Bare Magnet 1/4"Dia x 9/16" L (Also Available DC-1631 w/3/4" Gap)



DC-1671

1" Gap

18" Wire Leads / Crush Resistant 3/8" Diameter Rare earth Donut Magnet 10 Per Pack



DC-1651WG

3/8" Dia Stubby Press Fit / 3/4" L 12" Wire Leads / Crush Resistant 3/8" Stubby Magnet / 3/4" L



DC-1621WG

11/4" Gap

Standard 3/8" Dia Press Fit / 11/4" L 12" Wire Leads / Crush Resistant 3/8" Magnet / 11/4" L (Form C use Model - PS-1622) 10 Per Pack



PS-1650

1/2" Gap 3/8" Dia Stubby Press Fit / 1/2" L 18" Wire Leads / Crush Resistant



PS-1641

1/2" Gap

18" Wire Leads / Crush Resistant 3/8" Stubby Magnet / 1/2" L 10 Per Pack



DC-1641

13.5" Wire Leads / Crush Resistant 3/8" Magnet / 11/4" L

DC-1714

3/4" Roller Ball Switch with Spacer Normally Closed 22 Gauge Wired Output / 12" leads 3/4" Diameter x 111/16" L



DC-1813

3/4" Gap

1" Gap

3/4" Dia Steel Door Contacts / 1 1/16" L 12" Wire 22 Gauge Leads / Crush Resistant



DC-1814

3/4" Gap

3/4" Dia Steel Door Contacts / 1 1/6" L 12" Wire Leads / Crush Resistant

HIGH IMPACT MAGNETIC CONTACTS

High Impact means, no loss of performance due to adverse stress caused by building movement, sudden impacts, or temperature change.

PRESS FIT - TERMINALS







DC-2611 3/4" Gap

DC-2614 1/2" Gap

Terminal Wiring Connect / Crush Resistant 3/8" Diameter Rare Earth Donut Magnet

DC-2712

3/4" Push Button Switch with Spacer Normally Closed Terminal Output



DC-2612

1/2" Gap

Terminal Wiring Connect / Crush Resista 3/8* Diameter Rare Earth Donut Magnet 10 Per Pack

DC-2711

3/8* Press Fit Plunger Switch Normally Closed Loop Screw Terminal Alarm Output 3/8* Diameter x 1 3/4* L







3" Gap PS-2023

Overhead Door Contact W/ 27* Armored Cable 4 1/8" L x 11/2" W x 3/8" H / Bracket - 5 1/4" L x 2" x 2" Armored Magnet w/ Adjustable Bracket Form A / NC Alarm Output

DC-4811

2.75" Gap

Track Mount Mount Panel Door Contact Switch Includes L bracket to fit tracks up to 3" Wide



PS-2022

3" Gap

Overhead Door Contact W/ 27* Armored Cable 4 1/8* L x 11/2* W x 3/8* H / Bracket - 5 1/4* L x 2* x 2* Armored Magnet Form C / NC - NO Alarm Output 1 unit per pack

ACCESSORIES



DC-SP01 3/4" to 3/8" Adaptor

White, Brown or Grey 100 Per Pack



DC-SP02 3/8" Plug

White, Brown or Grey 100 Per Pack

Aleph provides more than 40 years of leading-edge technology and state-of-the-art manufacturing techniques to the electronics and security industries. As a wholly owned subsidiary of Tokyo, Japan-based Nippon Aleph, a world-class corporation with sales exceeding \$240 million, dealers and installers rely on Aleph products for the highest quality and most competitive pricing. Aleph continues to earn the highest reputation for zero defects, QS 9000, ISO 14001, ISO 9001, ISO 9002, and ISO 9003 manufacturing standards, and an absolute commitment to deliver the most reliable products in the industry.

Look for the complete family of Aleph professional security products at a security distributor near you.



Call European Head Office: Call UK Sales Office:

+31(0)20 7779 520 +44(0)1933 670987

Website

infoEurope@aleph-cn.com

